




BARRE ROND/CARRÉ CUIVRE



Alliage CUA1 – ETP – CW004A
Norme EN 13601
Longueurs courantes de fabrication 4 ml



Diam m/m Poids kg/m

3	0,06
4	0,11
5	0,17
6	0,25
7	0,34
8	0,44
9	0,56
10	0,70
12	1,01
14	1,37
15	1,57
16	1,78
18	2,16
20	2,80
22	3,38
25	4,37
28	5,48
30	6,29
32	7,16
35	8,56
40	11,18
42	12,33
45	14,15
50	17,48
55	21,14
60	25,16
65	29,53
70	34,25
75	38,20
80	44,74
90	56,62
100	69,87
110	85,00
115	92,40
120	101,00
130	118,00
140	137,00
150	157,00
160	179,00
180	226,00
200	280,00
250	437,00

Section m/m Poids kg/m

6 x 6	0,32
8 x 8	0,57
10 x 10	0,89
12 x 12	1,28
15 x 15	2,00
16 x 16	2,28
18 x 18	2,88
20 x 20	3,56
25 x 25	5,56
30 x 30	8,01
35 x 35	10,90
40 x 40	14,24
50 x 50	22,25
60 x 60	32,04
70 x 70	43,61
80 x 80	56,96
90 x 90	72,10
100 x 100	89,96
120 x 120	128,20
140 x 140	174,50